



SAM-40

Two needle, Post bed, Large vertical axis hook, Multi different ornamental stitching, Automatic presser foot lift, Compound feed and walking foot, Lockstitch sewing machines





Applications

- For sewing medium to heavy weight materials such as leather, vinyl, synthetics and laminated and coated materials
- Suitable for sewing such as automobile upholstery tarpaulins, covers, awnings, tents, umbrellas, handbags, luggage, travelware accessories, sports and camping equipment and wearing apparel outdoor clothing.



SAM-40

Features

- Wide range of ornamental stitch
 - * 12 standard stitch patterns
 - * User designed stitch patterns can be registerd (Max.99 patterns)
- Easy operation of stitch pattern change by touch panel display
- Max.10mm stitch length



	XXXX	40% J
() XXXX	XIXIXIXI	
[XIX]		

Touch panel display and 12 standard stitch patterns



Specifications

Variety		SAM-40	
Number of needle		Two needle	
Max. sewing speed		450 s.p.m.	
Max.stitch length		10 mm	
Clearance under	, , , , , , , , , , , , , , , , , , ,	9 mm	
presser foot	by automatic foot lifter	16 mm	
Needle bar stroke		34 mm	
Needle		PF x 134KS #21 - #23 (Standerd #23)	
Thread		#20 - #1 (Standard #5)	
Hook		Large vertical axis hook (2.0 times)	
Post height		178 mm	
Thread take up lever		Link type	
Amount of walking foot movement		1 - 7mm	
Walking foot movement change switch		By touch panel display	
Bobbin winder		Built-in type located at the top of the sewing machine	
Auto presser foot lifting device		Pneumatic	
Safety device		Standard	
Lubrication		Semi-automatic lubrication type	
Bed size		475 x 178 mm	
Working space		260 x 120 mm	
Motor		AC Servo motor	

NOTE: (1) Speed depends on threads, materials and type of operation (2) Specifications subject to change without notice



SEIKO SEWING MACHINE CO., LTD. 2-13-6, Sakaecho, Funabashi-shi Chiba Prefecture, 273-0018, Japan Phone: +81-47-420-3561 (Overseas dept.) Fax : +81-47-420-3560 E-mail : export@seiko-sewing.co.jp

	Printed in Japan 2016.04			
http://www.seiko-sewing.co.jp/				